



Miniature LED Alphanumeric Route Indicator (Stencil)

Benefits

- > Network Rail Product Acceptance No PA05/01071
- > LED technology gives a long and predictable service life
- > Made to specific customer requirements
- > Available either single or double sided
- > All indications are lamp proved
- > Readability to category 3 – 100m

MINIATURE LED ALPHANUMERIC ROUTE INDICATOR (STENCIL)

<u>PADS No</u>	<u>Dorman Part No</u>	<u>Description</u>
086/021020	S/(Special)-/1S	LED Miniature Alphanumeric Route Indicator (Stencil), 110V, Single sided, (display to be specified by customer) with 1, 2, 3 or 4 Indications
086/021022	S/RA-----/1S	LED Miniature Alphanumeric Route Indicator (Stencil), 110V, Single sided "RA"
086/021023	S/OFF-----/1S	LED Miniature Alphanumeric Route Indicator (Stencil), 110V, Single sided "OFF"
086/021024	S/CD-----/1S	LED Miniature Alphanumeric Route Indicator (Stencil), 110V, Single sided "CD"
086/021025	S/CD:RA-----/1S	LED Miniature Alphanumeric Route Indicator (Stencil), 110V, Single sided "CD + RA"
<hr/>		
086/021021	S/(Special)-/1D	LED Miniature Alphanumeric Route Indicator (Stencil), 110V, Double sided (display to be specified by customer) with 1, 2, 3 or 4 Indications

Compliances

Railway Group Standards	GK/RT0031
Network Rail	BR 1651 Part 2

Approvals

Unrestricted Network Rail Certificate Nos. Stencil Indicator	PA05/01071
---	------------

Key Specifications

Operating Temperature Range	- 25°C to + 40°C
Nominal Operating Voltage	110Vac
Operating Voltage Range	Max 121Vac Min 88Vac
Nominal Operating Current	300mA @ 110Vac
Sealing of LED modules	IP65
Single Sided Indicator Weight	14kg
Double Sided Indicator Weight	27kg

Max No of Indications per Indicator

Below are examples of the maximums for bespoke double sided stencil indications	
S/1:2:3:4---/1S	4 single character indications
S/A:B:C:D---/1S	4 single character indications
S/DM:DR:UR--/1S	3 – two character indications
S/SG1:SG2---/1S	2 – three character indications

Below is an example of the **maximums** for the bespoke double sided stencil indications
S/OFF-----/1D

Advice on the complexity of the indications to be sought from Dorman prior to ordering

DORMAN
 Wennington Road
 Southport
 Merseyside
 UK PR9 7TN
 T: +44 (0) 1704 518000
 F: +44 (0) 1704 518001
 E: sales@dorman.co.uk
 www.dorman.co.uk



Certificate No. FM14371